



- Container Anchor post is meant to provide a temporary anchor for working on top of 20 ft & 40 ft shipping containers.

- In addition to be used as a stand alone anchor post, it can also be used to form a horizontal life line over the top of container depending upon the requirement of work to be done.

- Provides an elevated anchorage point, which reduces fall clearance.

- Comes with a side lock & tag line arrangement for secure installation by one person only.

- Can be removed without damaging the container.

- Has an anchorage allowing a 360° rotation (diam. of the anchorage eye: 20 mm, suitable for most of the connectors).

- **Minimum breaking strength of the system: 12kN.**

Compliance: EN 795:2012 Type B.

Material of components:

Steel

Height:		Weight:
925 mm		14.53 kg

KRATOS SAFETY

689 Chemin du Buclay
38540 Heyrieux – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

CARTON SIZE / PCS.

1 pc

AET N°

DOLOMITICERT SCARL, N°2008

Zona Industriale Villanova
32013 Longarone (BL), Italia

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom